



VHF MARINE TRANSCEIVERS

IC-M1V IC-M1EURO V



Meets

MIL-STD 810

*The world's smallest waterproof marine radio!***

Ultra compact, waterproof transceiver

Icom's IC-M1V is the smallest and lightest waterproof* marine handheld available. Plus, it features non-corrosive construction.

*equivalent to JIS waterproof specification grade 7 (1m depth for 30 min.)

Powerful 5 watts of talk power

The first in its class to use a powerful Lithium Ion battery, the IC-M1V's 5 watts can carry a conversation a long way. Charging is easy; with Lithium Ion, there's no need to fully discharge before recharging, as should be done with Ni-Cds.

Lithium Ion power = long battery life

With typical operation*, you'll get an incredible 15 to 16 hours of operating time— nearly 2 times longer than most Ni-Cds. Lithium Ion stores a charge more than 3 times longer than a typical Ni-Cd, too!

*Tx:Rx: Stand-by duty ratio = 5:5:90 with BP-215L

Waterproof speaker-microphone operation

A waterproof* speaker-microphone plugs right in to the waterproof jack on top of the IC-M1V. Go where its wet without fear!

*equivalent to JIS waterproof specification grade 7 (1 m depth for 30 min.)

Extra large LCD with alphanumeric indications

A large, backlit LCD offers easy to read channel numbers and descriptions. Read the IC-M1V's built-in channel descriptions, or program in your own! With up to 10 alphanumeric characters per channel, its easy to customize channel descriptives.

Flexible battery charging

Charge the IC-M1V on a boat, at home, or in the car. A self-standing battery charger comes with the radio set the charger on top of a table, or mount it to a wall. The charger accepts a variety of DC power sources*, or use the included AC adapter.

*Optional charging cable required

Fast scanning functions

"TAG" scanning offers easy, one touch channel selection and deslection. Advanced dual and tri watch scanning, normally reserved for more expensive radios, is also available.

**As of 10/99

Icom Inc.

ADDITIONAL FEATURES

- The self check function checks internal temperature, connected battery voltage (over voltage detection), PLL lock and water intrusion
- Battery indicator shows remaining battery power in 4 levels
- Auto WX scan and WX Alert function (USA version only)
- Simple Up/Down switches for operating channel selection
- Instant access to Ch 16 and programmable call channel

- 2 step power saver
- Key lock function
- Automatic LCD and key backlight
- Up to 22 free channels are available (ask your local dealer for details)
- Optional voice scrambling capability (Not available in some countries)
- ATIS standard for German version

SPECIFICATIONS

GENERAL

- Frequency range (MHz) :
Tx 156.025–157.425
Rx 156.025–163.275
- Usable channels* : All U.S.A., International and Canadian channels; plus 10 weather channels (U.S.A. only)
- Mode : 16K0G3E (FM)
- Power supply requirement : 7.4V DC (BP-215/L)
- Current drain (at 7.4V DC) :
Tx (at 5W output) 1.5A
Rx (at AF max.) 200mA
(at Stand-by) 20mA
- Operating temp. range : –20°C to +60°C;
–4°F to +140°F
- Antenna connector : SMA (50Ω)
- Dimensions : 52.5(W)×129(H)×30(D);
(proj. not included; mm/in) 2½(W)×5¾(H)×1¾(D)
- Weight (approx.; with BP-215L): 280g; 9.9oz

Supplied accessories:

- Battery pack
- Battery charger
- AC adapter*
- Antenna
- Belt clip
- Hand strap

TRANSMITTER

- Output power* : 5.0W (Hi), 1.0W (Low) and 0.5W (Low2)
- Modulation system : Variable reactance frequency modulation
- Max. Frequency deviation : ± 5kHz
- Audio harmonic distortion : Less than 10% (at 60% mod.)
- Spurious emissions :
IC-M1V Less than –65dB
IC-M1EURO V 0.25μW

RECEIVER

- Intermediate frequencies : 1st 21.7MHz
2nd 450kHz
- Sensitivity :
IC-M1V (12dB SINAD) Less than 0.35μV
IC-M1EURO V (20dB SINAD) 1.0μV typical (emf)
- SQL sensitivity (at threshold):
IC-M1V Less than 0.35μV
IC-M1EURO V Less than 0.71μV
- Adjacent Ch. selectivity :
IC-M1V 70dB typical
IC-M1EURO V 70dB

- Spurious response :
IC-M1V 70dB typical
IC-M1EURO V 70dB
- Intermodulation rejection ratio:
IC-M1V 70dB typical
IC-M1EURO V 68dB
- Hum and noise ratio : More than 40dB
- Audio output power : 0.35W (typical at 10% distortion with an 8Ω load)

* Varies according to version

Applicable U.S. Military Specifications

Icom makes rugged products that meet MIL-STD requirements and strict environmental standards as follows.

Standard	MIL 810C		MIL 810D		MIL 810E	
	Method	Proc.	Method	Proc.	Method	Proc.
High Temp.			501.2	II	501.3	II
Low Temp.			502.2	II	502.3	II
Humidity	507.1	I	507.2	II	507.3	II
Vibration	514.2	VIII, X	514.3	I	514.4	I
Shock	516.2	I, II, V	516.3	I, IV	516.4	I, IV

The IC-M1EURO V meets EMC directive. Specifications for the IC-M1V and the IC-M1EURO V are measured in accordance with EIA-152C & EIA-204D(E) and EN301-178, respectively. All stated specifications are subject to change without notice or obligation.

OPTIONS

BP-215L Li-Ion BATTERY PACK

7.4V/1800mAh rechargeable battery pack provides 15–16 hours operating time.
(Tx/Rx: Stand-by=5:5:90)
Same as supplied with the transceiver.

AD-95 BATTERY CHARGER

+ **BC-122A/E/V** AC ADAPTER
Regularly charges the BP-215L in 10 hours (max.). Same as supplied with the transceiver.

BC-119N DESKTOP CHARGER

+ **AD-102** CHARGER ADAPTER
+ **BC-145A/E/V** AC ADAPTER
For rapidly charging of a battery pack. Charging time: 1.5–2 hours (approx).

BC-121N MULTI-CHARGER

+ **AD-102** CHARGER ADAPTER
+ **BC-124** AC ADAPTER
For rapidly charging of up to 6 batteries simultaneously. Charging time: 1.5–2 hours (approx)

CP-17L CIGARETTE LIGHTER CABLE

or **OPC-515L** DC POWER CABLE
For use the AD-95 or BC-119N with a DC power supply.

OPC-656 DC POWER CABLE

For use the BC-121N with a DC power supply.

HM-125 SPEAKER-MICROPHONE

Waterproof construction, corresponds to JIS grade 7 (1 m/30 min.). An alligator type clip.

MB-88 SWIVEL BELT CLIP

Prevents accidental dropping from your belt.

UT-98 (Ver. 02) VOICE SCRAMBLER UNIT

Ensures private communications. 128 scrambling codes are available. The scrambling system is not compatible with UT-112.

UT-112 VOICE SCRAMBLER UNIT

Total of 32 scrambling codes available for ensuring private communication. The scrambling system is not compatible with UT-98.

* Voice scrambling units are not available in some countries. Ask your dealer for detail.

BP-215L



BC-122A/E/V



AD-95



BC-124

BC-121N
+AD-102
(6 pcs.)

BC-119N+AD-102+BC-145

MB-88



HM-125



Icom Inc.

1-1-32, Kamiminami, Hirano-ku, Osaka 547-0003, Japan Phone: 06 6793 5302 Fax: 06 6793 0013 URL: <http://www.icom.co.jp/world/index.html>

Count on us!

Icom America Inc.

<Corporate Headquarters>
2380 116th Avenue N.E., Bellevue, WA 98004, U.S.A.
Phone: (425) 454-8155 Fax: (425) 454-1509
URL : <http://www.icomamerica.com>
<Customer Service> Phone : (425) 454-7619

Icom Canada

Glenwood Centre #150-6165 Highway 17,
Delta, B.C., V4K 5B8, Canada
Phone: (604) 952-4266 Fax: (604) 952-0090
URL : <http://www.icomcanada.com>

Icom (Australia) Pty. Ltd.

A.B.N. 88 006 092 575
290-294 Albert Street, Brunswick, Victoria, 3056, Australia
Phone: 03 9387 0666 Fax: 03 9387 0022
URL : <http://www.icom.net.au>

Icom New Zealand

146A Harris Road, East Tamaki, Auckland, New Zealand
Phone: 09 274 4062 Fax: 09 274 4708
URL : <http://www.icom.co.nz>

Icom (Europe) GmbH

Communication Equipment
Himmelgeister Str. 100, D-40225 Düsseldorf, Germany
Phone: 0211 346047 Fax: 0211 333639
URL : <http://www.icomeurope.com>

Icom Spain S.L.

Ctra. de Gracia a Manresa Km. 14,750
08190 Sant Cugat del Valles Barcelona, SPAIN
Phone: (93) 590 26 70 Fax: (93) 589 04 46
URL : <http://www.icomspain.com>

Icom (UK) Ltd.

Unit 9, Sea St., Herne Bay, Kent, CT6 8LD, U.K.
Phone: 01227 741741 Fax: 01227 741742
URL : <http://www.icomuk.co.uk>

Icom France S.a

Zac de la Plaine, 1, Rue Brindejont des Moulins
BP 5804, 31505 Toulouse Cedex, France
Phone: (33) 5 61 36 03 03 Fax: (33) 5 61 36 03 00
URL : <http://www.icom-france.com>

Asia Icom Inc.

6F No. 68, Sec. 1 Cheng-Teh Road,
Taipei, Taiwan, R.O.C.
Phone: (02) 2559 1899 Fax: (02) 2559 1874
URL : <http://www.asia-icom.com>

Beijing Icom Ltd.

1305, Wanshang Plaza, Shijingshan Road,
Beijing, China
Phone: (010) 6866 6337 Fax: (010) 6866 3553
URL : <http://www.bjicom.com>



Certificate Number Q14190

Icom Inc. (Japan), is an ISO9001 certification acquired company.

Your local distributor/dealer: